

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 2020822

Revision Number 0

Revision Date: 20260822

Standard SDS begins on the following page.

This page is provided to customers for their assistance and is not part of the Standard Safety Data Sheet.

Product: SafetyCool SC-100	Manufacturer: Engineered Fluids, Inc. 4917 Profit Drive, Tyler, TX 75707 USA +1-725-281-1921
--	--

General Description: Synthetic hydrocarbon heat transfer fluid

Here is a Quick Guide to Important Information Contained in the SDS:

Characteristic	SC-100	SDS Section
Toxicity	Nontoxic to Humans	Section 11
Handling	Use Personal Protective Equipment	Section 7.1 + 8.2.2
In Case of Spills	Treat as a biodegradable light oil	Section 6
In case of Fire	Treat as a light hydrocarbon oil.	Section 5
Transportation	Not Regulated	Section 14
Biodegradation	Biodegradable	Section 12.2
WGK - Wassergefährdungsklasse WHC - Water Hazard Class	WGK =1 (Low Hazard)	Section 15

Emergency Telephone Number: +1-352-323-3500 Available 24 hours
Factory Telephone Number: +1-725-218-1981 Available 8-5 CST

National Fire Protection Diamond advisory for this product is:

BLUE IS HEALTH HAZARD
"0" is the lowest hazard class

RED is FIRE HAZARD
"1" means that this material will ignite, but with difficulty.

YELLOW IS REACTIVITY WITH OTHER CHEMICALS
"0" indicates that this material is stable

The GHS Communication Standard requires that all hydrocarbon based chemicals be designated a Category 1 Aspiration Hazard if they have a kinematic viscosity ≤ 20.5 cSt. @ 40C. This includes some of our Dielectric Coolants, regardless of all other characteristics (including their biodegradation, non-toxicity, and food grade certification)

These products do not pose a toxicity risk if small amounts are ingested by mouth. However, the standardized wording does not make this differentiation clear and requires the statement even though there is little health risk posed by swallowing. The most probable hazard related to aspiration posed by EC-100 is the inhalation of a "mist" of the product.

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : SC-100 Dielectric Coolant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Dielectric Coolant Fluid for use in closed circulating systems.

1.2.2. Uses advised against

Restrictions on use : For professional use only.
Do not expose to fire or flame.

1.3. Details of the supplier of the safety data sheet

Supplier

Engineered Fluids, Inc.
4917 Profit Drive
Tyler, Texas 75707 USA
T +1-281-766-4501
support@engineeredfluids.com

1.4. Emergency telephone number

Emergency number : Call Infotrac, Inc., 1-352-323-3500

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501

Revision Number 0

Revision Date: 20250501

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category H304

Flammable Liquid Category 4 H227

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

:



GHS08

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H304 - May be fatal if swallowed and enters airways.

Precautionary statements (CLP)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Extra phrases

: For professional users only.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naptha (petroleum), hydrotreated, heavy	CAS-No.: 64742-48-9 EC-No.: 265-149-8	100	Asp. Tox. 1, H304 Flam Liq 4, H227

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung edema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry powder. Carbon dioxide. Sand. Fire-Fighting Foam
Unsuitable extinguishing media	: Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable cleaning Coolant; Flash Point 92C
-------------	---

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501

Revision Number 0

Revision Date: 20250501

Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Store locked up.
Storage temperature : 0 – 40 °C
Packaging materials : Store always product in container of same material as original container.
Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids
Joint storage table :

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7
Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2
Joint storage permitted for : LGK 2B, LGK 3, LGK 4.1B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Naptha (petroleum), hydrotreated, heavy	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Destillate (Erdöl), mit Wasserstoff behandelt leichte (C9 – C14 Aliphaten)
AGW (OEL TWA)	Siehe TRGS 900, Nummer 2.9
Remark	AGS - Ausschuss für Gefahrstoffe; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501

Revision Number 0

Revision Date: 20250501

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501

Revision Number 0

Revision Date: 20250501

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Liquid.
Odour	: None
Odour threshold	: Not available
Melting point	: Not applicable – liquid mixture at application temps
Freezing point	: ,-30C
Boiling point	: 160 °C
Flammability	: Flammable
Explosive limits	: LEL: 0.5%, UEL: 6.5%
Lower explosion limit	: 0,5 vol %
Upper explosion limit	: 6,5 vol %
Flash point	: 91 °C
Auto-ignition temperature	: >200C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 1.2 cSt (mm/sec^2) @ 20C
Viscosity, dynamic	: 1 mPa·s ,20 °C, 1.5 cSt @ 40C
Solubility	: Water: Not miscible in water.
Partition coefficient n-octanol/water (Log Kow)	: >12
Vapour pressure	: 0.3 mm Hg @ 20C
Vapour pressure at 50°C	: Not available
Density	: 0.811 g/cm³ (6.76 lbs/gal)
Relative density	: 0.81
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable
VOC content	: 811 g/liter

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials. Avoid temperatures $>50^{\circ}\text{C}$.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Naptha (petroleum), hydrotreated, heavy	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1000 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5,28 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The substance/mixture has no endocrine disrupting properties.

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Not rapidly degradable

Naptha (petroleum), hydrotreated, heavy	
LC50 96h - Fish [1]	2 – 5 mg/l
EC50 48h - Crustacea [1]	1,4 mg/l
EC50 72h - Algae [1]	1 – 3 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501

Revision Number 0

Revision Date: 20250501

12.5. Results of PBT and vPvB assessment

Dielectric Coolant SC-100

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.
HP Code : HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1268	UN 1268	UN 1268	UN 1268	UN 1268
14.2. UN proper shipping name				
UN1268 Petroleum distillates, n.o.s., COMBLIQ, III	UN1268 Petroleum distillates, n.o.s., COMBLIQ, III	UN1268 Petroleum distillates, n.o.s., COMBLIQ, III	UN1268 Petroleum distillates, n.o.s., COMBLIQ, III	UN1268 Petroleum distillates, n.o.s., COMBLIQ, III

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN1268 Petroleum distillates, n.o.s., COMBLIQ, III	UN1268 Petroleum distillates, n.o.s., COMBLIQ, III	UN1268 Petroleum distillates, n.o.s., COMBLIQ, III	UN1268 Petroleum distillates, n.o.s., COMBLIQ, III	UN1268 Petroleum distillates, n.o.s., COMBLIQ, III
14.3. Transport hazard class(es)				
3 - Class 3 - Combustible liquid 49 CFR 173.120	3 - Class 3 - Combustible liquid 49 CFR 173.120	3 - Class 3 - Combustible liquid 49 CFR 173.120	3 - Class 3 - Combustible liquid 49 CFR 173.120	3 - Class 3 - Combustible liquid 49 CFR 173.120
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Not expected to be dangerous to the environment	Not expected to be dangerous to the environment	Not expected to be dangerous to the environment	Not expected to be dangerous to the environment	Not expected to be dangerous to the environment
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

Special provisions for carriage - Loading, : CV13
unloading and handling (ADR)

Tunnel restriction code (ADR) : -
EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

Packing instructions (RID) : P001, IBC03, LP01, R001
 Special packing provisions (RID) : PP1
 Mixed packing provisions (RID) : MP19
 Portable tank and bulk container instructions (RID) : T4
 Portable tank and bulk container special provisions (RID) : TP1, TP29
 Tank codes for RID tanks (RID) : LGBV
 Transport category (RID) : 3
 Special provisions for carriage – Packages (RID) : W12
 Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
 Colis express (express parcels) (RID) : CE8
 Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Dielectric Coolant SC-100 ; Distillates (petroleum), hydrotreated heavy light	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501

Revision Number 0

Revision Date: 20250501

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Germany

- | | |
|--|---|
| Employment restrictions | : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG). |
| Water hazard class (WGK) | : WGK 1, Low hazard to water (Classification according to AwSV, Annex 1). |
| Hazardous Incident Ordinance (12. BImSchV) | : Is not subject of the Hazardous Incident Ordinance (12. BImSchV) |

Netherlands

- | | |
|--|--|
| ABM category | : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioaccumulative potential/ toxicity or persistence) |
| SZW-lijst van kankerverwekkende stoffen | : Distillates (petroleum), hydrotreated light [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).] is listed |
| SZW-lijst van mutagene stoffen | : Distillates (petroleum), hydrotreated light [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).] is listed |
| SZW-lijst van reprotoxische stoffen – Borstvoeding | : None of the components are listed |
| SZW-lijst van reprotoxische stoffen – Vruchtbaarheid | : None of the components are listed |
| SZW-lijst van reprotoxische stoffen – Ontwikkeling | : None of the components are listed |

Denmark

- | | |
|-----------------------|---------------|
| Class for fire hazard | : Class III-1 |
| Store unit | : 50 liter |

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501

Revision Number 0

Revision Date: 20250501

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501

Revision Number 0

Revision Date: 20250501

Abbreviations and acronyms:

OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

CIRS-EU-2023

SC-100 Dielectric Coolant



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Ref: CSSS-TCO-010-155483

Issue Date: 20250501 Revision Number 0 Revision Date: 20250501

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.